

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
May 12, 2025

01 00 [3554]

PRODUCT NUMBER

V146129

PRODUCT NAME

KWIK-CLAW Fast Dry Conversion Varnish Primer, Clear

MANUFACTURER'S NAME

M. L. CAMPBELL
101 W. Prospect Avenue
Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

V146129 = | Acute | Chronic | Fire |

Product Weight

8.35 lb/gal

Specific Gravity

1.00

FLASH POINT

65 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
2-Propanol 67-63-0	N	N	N	N	1	1
1-Butanol 71-36-3	N	Y	Y	N	9	12
2-Methyl-1-propanol 78-83-1	N	Y	N	N	3	3
Acetone 67-64-1	N	Y	N	N	5	7
Ethyl Acetate 141-78-6	N	Y	N	N	11	13
n-Butyl Acetate 123-86-4	N	Y	N	N	30	34

Volatile Organic Compounds - U.S. EPA / Canada

	V146129	
	LB/Gal	g/L
Coating Density	8.35	1000
	By wt	By vol
Total Volatiles	60.8%	70.9%
Federally exempt solvents		
Water	0.1%	0.0%
Acetone	5.2%	6.6%
Organic Volatiles	55.5%	64.3%
Percent Non-Volatile	39.2%	29.1%
VOC Content	LB/Gal	g/L
Total	4.63	555
Less exempt solvents	4.96	594
Of solids	15.92	1907
Of solids	1.41 lb/lb	1.41 kg/kg
	By wt	
By wt LVP-VOC	55.5%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.80**

Volatile Organic Compounds - California

	V146129	
	LB/Gal	g/L
Coating Density	8.35	1000
	By wt	By vol
Total Volatiles	60.8%	70.9%
Exempt solvents		
Water	0.1%	0.0%
Acetone	5.2%	6.6%
Organic Volatiles	55.5%	64.3%
Percent Non-Volatile	39.2%	29.1%
VOC Content	LB/Gal	g/L
Total	4.63	555
Less exempt solvents	4.96	594
Of solids	15.92	1907
Of solids	1.41 lb/lb	1.41 kg/kg
	By wt	
By wt LVP-VOC	55.5%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.74**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	V146129	
	LB/Gal	g/L
Coating Density	8.35	1000
	By wt	By vol
Total Volatiles	60.8%	70.9%
Exempt solvents		
Water	0.1%	0.0%
Acetone	5.2%	6.6%
Organic Volatiles	55.5%	64.3%
Percent Non-Volatile	39.2%	29.1%
VOC Content	LB/Gal	g/L
Total	4.63	555
Less exempt solvents	4.96	594
Of solids	15.92	1907
Of solids	1.41 lb/lb	1.41 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	V146129	
	By wt	By vol
Total Volatiles	60.8%	70.9%
VOC Content	LB/Gal	g/L
Total	5.06	607

Volatile Organic Compounds - EU Directive 2010/75/EU

	V146129	
	By wt	By vol
Total Volatiles	60.8%	70.9%
VOC Content	LB/Gal	g/L
Total	5.06	607

Volatile Organic Compounds - Mexico

	V146129	
	LB/Gal	g/L
Coating Density	8.35	1000
	By wt	By vol
Total Volatiles	60.8%	70.9%
Exempt solvents		
Water	0.1%	0.0%
Acetone	5.2%	6.6%
Organic Volatiles	55.5%	64.3%
Percent Non-Volatile	39.2%	29.1%
VOC Content	LB/Gal	g/L
Total	4.63	555
Less exempt solvents	4.96	594
Of solids	15.92	1907
Of solids	1.41 lb/lb	1.41 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	V146129	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

7.16 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.