



PV15GR36



Door Bottom Replacement Vinyl

Use On: Vinyl Door Bottoms:
209_V

- Renews Effectiveness of Door Bottom Shoe
- Replaces Worn-Out Vinyl
- Saves Energy by Keeping Weather Outside



209_V


PV15GR36
Gray



LENGTH
36" (0.9 m)

DOOR BOTTOM REPLACEMENT VINYL

USE ON:



209_V

Installation Instructions:

1. Remove door shoe.
2. Loosen vinyl (use flat blade of screwdriver to pry up aluminum lip which retains the vinyl).
3. Remove old vinyl.
4. Clean all dust and dirt out of retainer grooves which hold vinyl in place.
5. Slip in new vinyl.
6. Re-retain vinyl by crimping aluminum retainer with pliers.
7. Re-install door shoe and adjust for an even seal. Crimp ends to hold in place.



ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions

UNITED STATES:

MEMPHIS, TN
Ph: 800.824.3018
Fax: 800.243.3656

VENTURA, CA
Ph: 800.283.9988
Fax: 800.283.4050

CANADA:

VANCOUVER, BC
Ph: 877.535.7888
Fax: 877.535.7444

TORONTO, ON
Ph: 866.243.9816
Fax: 866.243.9817