

POCKET DOOR SYSTEM (INSET)

ALT-ST15-D360


LATERAL OPEN  
CABINET HARDWARE

POCKET DOOR SYSTEM




- Create a clean design with doors that can conveniently pocket away.
- Can manage doors up to 63" (1600mm) tall weighing up to 33 lbs (15 kg).
- 5-speed adjustable soft-closing dampers (Uses 360 Olympia Hinges).
- 5-stage angle adjustment eliminating sagging doors.
- L-Shaped connecting plate minimizing racking and reduces door sag.
- Available slide lengths: 16", 19", 22", 24" and 28".
- Durability: successfully passed 40,000 open/close private cycles.

Installation




Easy Door Alignment Adjustment




When installing, you can adjust the hanging angle just by lifting up the door.

Installation Example (Key on page 591)



- Number of slides
- S type : 2 pairs
- M type : 2 pairs
- L type : 4 pairs
- LL type : 4 pairs

Door Cut Out Dimensions



Last Digits of Item Name (Parts Set)	Door Storage Amount	Min. Cabinet Depth
16	12-7/16" (316 mm) + Thickness	16-1/4" (412 mm) + Thickness
19	15-7/16" (392 mm) + Thickness	19-3/16" (488 mm) + Thickness
22	18-7/16" (468 mm) + Thickness	22-3/16" (564 mm) + Thickness
24	20-7/16" (519 mm) + Thickness	24-3/16" (615 mm) + Thickness
28	24-7/16" (621 mm) + Thickness	28-1/4" (717 mm) + Thickness

	ALT-ST15-D360S (2 slides)	ALT-ST15-D360M (2 slides)	ALT-ST15-D360L (4 slides)	ALT-ST15-D360LL (4 slides)
Door Width	Max. 24" (610 mm)			
Door Height	19-11/16"~27-9/16" (500 - 700 mm)	27-9/16"~35-7/16" (700 - 900 mm)	35-7/16"~47-1/4" (900 - 1200 mm)	47-1/4"~63" (1200 - 1600 mm)
Door Thickness	11/16"~1-3/16" (18 - 30 mm)			
Door Weight	Max. 19.8 lbs (9 kg)		Max. 33 lbs (15 kg)	

Type	Hinge Placement			Slide Placement	
	A	B	C	D	E
S Type	14-3/16" (360 mm)	-	10-1/4" (260 mm)	-	-
M Type	22-1/16" (560 mm)	-	18-1/8" (460 mm)	-	-
L Type	14-15/16" (380 mm)	14-15/16" (380 mm)	10-1/4" (260 mm)	5-1/2" (140 mm)	10-1/4" (260 mm)
LL Type	20-7/8" (530 mm)	20-7/8" (530 mm)	16-15/16" (430 mm)	3-15/16" (100 mm)	16-15/16" (430 mm)



# ALT-ST15-D360 Parts Set Details















The following 1-19 show detailed information on the set codes included on the previous page.

No.	Qty				Parts	Dimensions	Item Name																																									
	S	M	L	LL																																												
1	2	4	<p>The item number with the same last digits as those of the set item number is included in each set. Mount the track so that the catch mounting side mark is located on the front side of the cabinet.</p>		<p>5/16" (7.5 mm) Travel length 3/16" (5 mm) 3-1/8" (80 mm) 2-1/16" (53 mm) 1-3/8" (35.5 mm) 1/2" (13.5 mm) Bumper 11/16" (17.5 mm) Access hole 3/8" (9.5 mm) Catch mounting side mark 1/8" (2.5 mm) Bumper 1/8" (3.5 mm) Outer member 1/8" (2.5 mm) 4xM4 clinching nut 1/2" (12 mm) Slide length 4.5x5.3 slotted hole 1-3/8" (35.3 mm) M4 clinching nut 5/8" (15.9 mm) Retainer 1/2" (12 mm) Inner member Steel ball</p>	AL80C-16																																										
						AL80C-19																																										
						AL80C-22																																										
						AL80C-24																																										
						AL80C-28																																										
						<table border="1"> <thead> <tr> <th>Item Name</th> <th>Slide Length</th> <th>Travel Length</th> <th>Door Storage</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>AL80C-16</td> <td>16-3/16" (411.4 mm)</td> <td>12-7/16" (316.4 mm)</td> <td>12-3/8" (315 mm)</td> <td>-</td> <td>15-1/4" (387.4 mm)</td> <td>14-5/8" (371.5 mm)</td> <td>10-5/8" (269.9 mm)</td> </tr> <tr> <td>AL80C-19</td> <td>19-3/16" (487.6 mm)</td> <td>15-7/16" (392.6 mm)</td> <td>15-3/8" (391 mm)</td> <td>17-3/16" (436.6 mm)</td> <td>17-3/16" (447.7 mm)</td> <td>13-5/8" (346.1 mm)</td> <td>9-1/8" (231.8 mm)</td> </tr> <tr> <td>AL80C-22</td> <td>22-3/16" (563.8 mm)</td> <td>18-7/16" (468.8 mm)</td> <td>18-3/8" (467 mm)</td> <td>21-1/4" (539.8 mm)</td> <td>20-5/8" (523.9 mm)</td> <td>16-5/8" (422.3 mm)</td> <td>10-5/8" (269.9 mm)</td> </tr> <tr> <td>AL80C-24</td> <td>24-3/16" (614.6 mm)</td> <td>20-7/16" (519.6 mm)</td> <td>20-3/8" (518 mm)</td> <td>23-1/4" (590.6 mm)</td> <td>22-5/8" (574.7 mm)</td> <td>18-5/8" (473.1 mm)</td> <td>11-5/8" (295.3 mm)</td> </tr> <tr> <td>AL80C-28</td> <td>28-3/16" (716.2 mm)</td> <td>24-7/16" (621.2 mm)</td> <td>24-7/16" (620 mm)</td> <td>28" (711.2 mm)</td> <td>26-5/8" (676.3 mm)</td> <td>22-5/8" (574.7 mm)</td> <td>13-5/8" (346.1 mm)</td> </tr> </tbody> </table> <p>Material: Steel Finish: Chromate</p>	Item Name	Slide Length	Travel Length	Door Storage	A	B	C	D	AL80C-16	16-3/16" (411.4 mm)	12-7/16" (316.4 mm)	12-3/8" (315 mm)	-	15-1/4" (387.4 mm)	14-5/8" (371.5 mm)	10-5/8" (269.9 mm)	AL80C-19	19-3/16" (487.6 mm)	15-7/16" (392.6 mm)	15-3/8" (391 mm)	17-3/16" (436.6 mm)	17-3/16" (447.7 mm)	13-5/8" (346.1 mm)	9-1/8" (231.8 mm)	AL80C-22	22-3/16" (563.8 mm)	18-7/16" (468.8 mm)	18-3/8" (467 mm)	21-1/4" (539.8 mm)	20-5/8" (523.9 mm)	16-5/8" (422.3 mm)	10-5/8" (269.9 mm)	AL80C-24	24-3/16" (614.6 mm)	20-7/16" (519.6 mm)	20-3/8" (518 mm)	23-1/4" (590.6 mm)	22-5/8" (574.7 mm)	18-5/8" (473.1 mm)	11-5/8" (295.3 mm)	AL80C-28	28-3/16" (716.2 mm)
Item Name	Slide Length	Travel Length	Door Storage	A	B	C	D																																									
AL80C-16	16-3/16" (411.4 mm)	12-7/16" (316.4 mm)	12-3/8" (315 mm)	-	15-1/4" (387.4 mm)	14-5/8" (371.5 mm)	10-5/8" (269.9 mm)																																									
AL80C-19	19-3/16" (487.6 mm)	15-7/16" (392.6 mm)	15-3/8" (391 mm)	17-3/16" (436.6 mm)	17-3/16" (447.7 mm)	13-5/8" (346.1 mm)	9-1/8" (231.8 mm)																																									
AL80C-22	22-3/16" (563.8 mm)	18-7/16" (468.8 mm)	18-3/8" (467 mm)	21-1/4" (539.8 mm)	20-5/8" (523.9 mm)	16-5/8" (422.3 mm)	10-5/8" (269.9 mm)																																									
AL80C-24	24-3/16" (614.6 mm)	20-7/16" (519.6 mm)	20-3/8" (518 mm)	23-1/4" (590.6 mm)	22-5/8" (574.7 mm)	18-5/8" (473.1 mm)	11-5/8" (295.3 mm)																																									
AL80C-28	28-3/16" (716.2 mm)	24-7/16" (621.2 mm)	24-7/16" (620 mm)	28" (711.2 mm)	26-5/8" (676.3 mm)	22-5/8" (574.7 mm)	13-5/8" (346.1 mm)																																									
2	1	<p>The end of the item number indicates the corresponding size.</p>		<p>Enlarged view of side [S, M types] Full length L [L, LL types] 11/16" (17.9 mm) 2-3/4" (70 mm)</p>	ALT-ST15-S																																											
					ALT-ST15-M																																											
					ALT-ST15-L																																											
					ALT-ST15-LL																																											
<table border="1"> <thead> <tr> <th rowspan="2">Item Name</th> <th colspan="2">Hinge Placement</th> <th colspan="3">Slide Placement</th> <th rowspan="2">Full Length L</th> </tr> <tr> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> </tr> </thead> <tbody> <tr> <td>ALT-ST15-S</td> <td>14-3/16" (360 mm)</td> <td>-</td> <td>10-1/4" (260 mm)</td> <td>-</td> <td>-</td> <td>16-1/8" (410 mm)</td> </tr> <tr> <td>ALT-ST15-M</td> <td>22-1/16" (560 mm)</td> <td>-</td> <td>18-1/8" (460 mm)</td> <td>-</td> <td>-</td> <td>24" (610 mm)</td> </tr> <tr> <td>ALT-ST15-L</td> <td>14-15/16" (380 mm)</td> <td>14-15/16" (380 mm)</td> <td>10-1/4" (260 mm)</td> <td>5-1/2" (140 mm)</td> <td>10-1/4" (260 mm)</td> <td>31-7/8" (810 mm)</td> </tr> <tr> <td>ALT-ST15-LL</td> <td>20-7/8" (530 mm)</td> <td>20-7/8" (530 mm)</td> <td>16-15/16" (430 mm)</td> <td>3-15/16" (100 mm)</td> <td>16-15/16" (430 mm)</td> <td>43-11/16" (1110 mm)</td> </tr> </tbody> </table> <p>Material: Aluminum Alloy Finish: Silver Anodized</p>	Item Name	Hinge Placement		Slide Placement			Full Length L	A	B	C	D	E	ALT-ST15-S	14-3/16" (360 mm)	-	10-1/4" (260 mm)	-	-	16-1/8" (410 mm)	ALT-ST15-M	22-1/16" (560 mm)	-	18-1/8" (460 mm)	-	-	24" (610 mm)	ALT-ST15-L	14-15/16" (380 mm)	14-15/16" (380 mm)	10-1/4" (260 mm)	5-1/2" (140 mm)	10-1/4" (260 mm)	31-7/8" (810 mm)	ALT-ST15-LL	20-7/8" (530 mm)	20-7/8" (530 mm)	16-15/16" (430 mm)	3-15/16" (100 mm)	16-15/16" (430 mm)	43-11/16" (1110 mm)								
Item Name		Hinge Placement		Slide Placement				Full Length L																																								
	A	B	C	D	E																																											
ALT-ST15-S	14-3/16" (360 mm)	-	10-1/4" (260 mm)	-	-	16-1/8" (410 mm)																																										
ALT-ST15-M	22-1/16" (560 mm)	-	18-1/8" (460 mm)	-	-	24" (610 mm)																																										
ALT-ST15-L	14-15/16" (380 mm)	14-15/16" (380 mm)	10-1/4" (260 mm)	5-1/2" (140 mm)	10-1/4" (260 mm)	31-7/8" (810 mm)																																										
ALT-ST15-LL	20-7/8" (530 mm)	20-7/8" (530 mm)	16-15/16" (430 mm)	3-15/16" (100 mm)	16-15/16" (430 mm)	43-11/16" (1110 mm)																																										

\*For information on how to mount the parts and the quantities of the parts included in each parts set, please see the instructions.

# ALT-ST15-D360 Parts Set Details













The following ①-⑬ show detailed information on the set codes included on the previous page.

No.	Qty				Parts	Dimensions	Item Name			
	S	M	L	LL						
③	2		3		Hinge body (with built-in damper) 		H360-D26-0T	Material: Steel Finish: Nickel		
④	2		3		Hinge mounting plate 		360-P4W-30T	Material: Steel Finish: Nickel		
⑤	2		3		Mounting plate 		ALT-MP30	Material: Stainless Steel Finish: Barrel Polished		
⑥	2		3		Guide roller 		ALT-GR	Material: Steel/Ethylene Propylene Rubber (EPDM) Finishing/Color: Nickel/White		
⑦ - ⑬	1				Parts set <div style="display: flex; flex-wrap: wrap; justify-content: space-around;"> <div style="text-align: center;">⑦ Catch </div> <div style="text-align: center;">⑧ Roller </div> <div style="text-align: center;">⑨ Roller bracket </div> <div style="text-align: center;">⑩ Insert female screw </div> <div style="text-align: center;">⑪ G-type sliding tack </div> <div style="text-align: center;">⑫ Adjustment bolt </div> </div>	S type M type	ALT-ST15-D10-MP	L type LL type	ALT-ST15-D10-LLP	Necessary types and numbers of screws and hexagon wrenches are included.

\*For information on how to mount the parts and the quantities of the parts included in each parts set, please see the instructions.  
\*<sup>1</sup> The mounting plates in the images and drawings are not included in the set.

# ALT-ST15, ALT-ST20 Parts Set Details

Detailed information on the parts sets used for ALT-ST15 and ALT-ST20

Qty		Parts	Dimensions	Item Name
S type	M type			
2		Catch 	 <p> <math>\phi 4.5</math> hole <math>\phi 9.2</math> countersunk depth 5.6  <math>1-3/16"</math> (29.4 mm)  <math>1/4"</math> (6.5 mm)  <math>1/4"</math> (5.5 mm)  <math>1/4"</math> (5.5 mm)  <math>3/4"</math> (19.2 mm)  <math>1/4"</math> (6.1 mm)  <math>15/16"</math> (23.2 mm)  <math>7/2"</math> (7.2 mm)                 </p>	AL127-CH  Material: Polyurethane (PUR) Color: Black
2		Roller 	 <p> <math>1/16"</math> (1 mm)  <math>13/16"</math> (<math>\phi 21</math> mm)  <math>3/8"</math> (9 mm)  <math>5/16"</math> (8 mm)  <math>1/8"</math> (2.5 mm)                      M6  <math>\phi 5/16"</math> (<math>\phi 8</math> mm)  <math>\phi 1/2"</math> (<math>\phi 12</math> mm)                 </p>	DU19-B4SBR  Material: Ethylene Propylene Rubber (EPDM)/Steel Finishing/Color: Gloss Chromate/White
Left/Right 1 each		Roller bracket* 	 <p> <math>\phi 4.2</math> hole  <math>1/4"</math> (6 mm)  <math>1-1/8"</math> (28 mm)  <math>5/8"</math> (16 mm)  <math>13/16"</math> (21 mm)  <math>1/8"</math> (3 mm)  <math>2 \times 4.2 \times 8.2</math> slotted hole  <math>3/8"</math> (9 mm)  <math>3/8"</math> (9 mm)  <math>5/16"</math> (8 mm)  <math>11/16"</math> (18 mm)  <math>5/16"</math> (8 mm)  <math>7/5"</math> (7.5 mm)                 </p> <p>† The drawing shows A type (bottom right/upper left)</p>	ALT-2V-AB † Type A (bottom right/ upper left)  ALT-2V-BB † Type B (upper right/bottom left)  Material: Steel Finish: Colored Chromate
2		Insert female screw* 	 <p> <math>\phi 7/16"</math> (<math>\phi 11</math> mm)                      M6  <math>1/2"</math> (13 mm)  <math>\phi 3/8"</math> (<math>\phi 9</math> mm)                 </p>	SC-107-13  Material: Polyamide (PA) Color: White
2		G-type sliding tack 	 <p> <math>11/16"</math> (17.5 mm)  <math>\phi 1/8"</math> (<math>\phi 3</math> mm)  <math>3/8"</math> (9 mm)  <math>1/16"</math> (1.8 mm)                 </p>	G-175  Material: Polyethylene (PE) Color: Natural
1	2	Adjustment bolt 	 <p> <math>1/8"</math> (3 mm)                      Hexagon hole                      Opposite side:  <math>1/8"</math> (3 mm)  <math>5/16"</math> (8 mm)  <math>\phi 1/2"</math> (<math>\phi 12</math> mm)  <math>3/16"</math> (4 mm)  <math>1/16"</math> (1.2 mm)  <math>3/8"</math> (10 mm)                      M5                 </p>	ALT-AB M5  Material: Steel (SWCH) Finishing/Color: Colored Chromate (Trivalent)/White Dedicated bolt for hanging adjustment

\*Use either roller bracket or insert female screw, depending on the mounting method.